



Counter Wall Cabinets

Installation Instructions

TOOLS AND SUPPLIES NEEDED

- ◆ Hammer
- ◆ Tape Measure
- ◆ Level
- ◆ Phillips Screwdriver
- ◆ Powered Drill and 3/32"
- ◆ Hacksaw or Fine Tooth Saw
- ◆ and 3/16" Drill Bits
- ◆ Sabre Saw or Circular Saw

FIRST

If this cabinet has a crown molding (packaged in separate box) install it according to the Linen Cabinet Crown Molding Attachment Instructions.

SECOND

Cut Backsplash off of the Laminate/Marble/Solid Surface Top

Hold the Linen Storage in place and mark the amount of the back splash to be removed. For laminate top - Cut from the front using a fine tooth saw. For marble top - Cut from the back side using a sabre saw or circular saw, using a carbide 40 plus tooth blade. In the case of a solid surface top use only a circular saw, using a carbide 40 plus tooth blade. For Quartz top— Use only a wet saw with a diamond blade.

THIRD

Locate and Drill Holes

Locate at least one stud where the cabinet will be mounted. Take the measurement(s) from a wall to the stud and transfer this measurement onto the cabinet back shelf support, considering the 1/2" thickness of cabinet end.

Drill stud mount holes using 3/16" drill bit.

Place cabinet in position and drill 3/32" pilot holes through all stud and General Mounting Holes that are to be used (see Figure 1).

Remove cabinet and drill a 3/16" hole in wall for those general (non-stud) screw locations that are to be attached using plastic anchors. Then insert the plastic anchors.

FOURTH

Mount to wall with screws

Place cabinet in position and screw in the two #8 screws provided using a Phillips screwdriver (see Figure 1).

If the wall is uneven such that the cabinet does not lay flat against wall, shims (cedar shingles or other thin wood) may be required between the wall and cabinet at the screw locations so that the doors will look aligned and work properly.

FIFTH

Adjust Adjustable Shelves and Install Door Pulls

Choose location of adjustable shelves and insert a plastic support into each hole at all four corners of shelf. Insert shelf into the four shelf clips.

Install cabinet pulls/knobs using the hardware and screws provided if not already factory installed.

Figure 1

